

Year	1900	1901	1902	1903	1904	1905	1906	1907	1908	1909	1910	1911	1912	1913	1914	1915	1916	1917	1918	1919	1920	1921	1922	1923	1924	1925	1926	1927	1928	1929	1930	1931	1932	1933	1934	1935	1936	1937	1938	1939	1940	1941	1942	1943	1944	1945	1946	1947	1948	1949	1950	1951	1952	1953	1954	1955	1956	1957	1958	1959	1960	1961	1962	1963	1964	1965	1966	1967	1968	1969	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100
1900	1901	1902	1903	1904	1905	1906	1907	1908	1909	1910	1911	1912	1913	1914	1915	1916	1917	1918	1919	1920	1921	1922	1923	1924	1925	1926	1927	1928	1929	1930	1931	1932	1933	1934	1935	1936	1937	1938	1939	1940	1941	1942	1943	1944	1945	1946	1947	1948	1949	1950	1951	1952	1953	1954	1955	1956	1957	1958	1959	1960	1961	1962	1963	1964	1965	1966	1967	1968	1969	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	

Serial No.:

Inventors: YOSHIDA, et al.

Foreign Application:

Country: Japan

October 28, 2001

Joshua Kamukha

Translator

Yoshiko Kawahara

TELEPHONE SET, REPEATING DEVICE AND RECORDING MEDIUM

FIELD OF THE INVENTION

The present invention relates to a repeating device, a telephone set and a recording medium, and especially relates to the communication technology of relaying via a communication line telephone devices connected to a local area network.

Heretofore, voice communication between dedicated telephone sets connectable to a local area network (hereinafter called LAN telephones) and voice communication between personal computers (PCs) connected to the local area network are realized by a VoIP (Voice over IP) technology that processes the voice signal into packets and transmits the packets through the network. As shown in FIG. 6, in a minimum system environment in which the LAN telephones and the repeating device operate, PCs 11 and telephone sets 12a - 12c connected to a receiver-side LAN 101 is connected via a router 14, an integrated services digital network (hereinafter called ISDN) 3, and connecting lines 41 and 42 to PCs 21 and telephone sets 22a - 22c connected to a caller-side LAN 20.

According to such system environment, the communication method realizing calls between LAN telephones connected either to the same local area network or to different local area networks having different subnet addresses via a subscriber line can be applied to connect calls that designate a specific address, but there is conventionally no transfer system that

enables the LAN telephone connected to a local area network to perform a transfer process.

SUMMARY OF THE INVENTION

The object of the present invention is to provide a telephone set, a repeating device, and a recording medium that enables a LAN telephone engaged in communication to transfer the communication to another LAN telephone connected to the same local area network or to a different local area network relayed by a communication line having a different subnet address.

The present invention provides a telephone connected to a local area network; said telephone comprising, during communication, a function for requesting a response from another receiver-side telephone indicating its availability to connect a call, and a function for notifying the address of the receiver-side telephone that responded to a caller-side telephone.

Moreover, the present invention provides a repeating device for relaying communication to a plurality of receiver-side telephones that are connected to a local area network; the repeating device comprising, upon receiving a transfer request from a user, a function for requesting a response from another receiver-side telephone indicating its availability to connect a call, and a function for notifying the address of the receiver-side telephone that responded to a caller-side telephone.

Even further, the present invention provides a recording medium readable by a computer and storing a program to be executed by said computer, said recording medium used either for a telephone being connected to a local area network or for a repeating device for relaying communication to a plurality of receiver-side telephones being connected to a local area network; wherein the program comprises either of the following sets of functions: upon receiving a transfer request from a user, a function for requesting a response from another receiver-side telephone indicating its availability to connect a call, and a function for notifying the address of the receiver-side telephone that responded to a caller-side telephone; or during communication, a function for requesting a response from another receiver-side telephone indicating its availability to connect a call, and a function for notifying the address of the receiver-side telephone that responded to a caller-side telephone.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is an explanatory view showing the functional structure of a logical block of the LAN telephone according to embodiment 1;

FIG. 2 is an explanatory view showing one example of the transfer operation performed by the LAN telephone according to embodiment 1;

FIG. 3 is an explanatory view showing an example where the

transfer cannot be performed by the LAN telephone according to embodiment 1;

FIG. 4 is an explanatory view showing the functional structure of a logical block of the repeating device according to embodiment 2;

FIG. 5 is an explanatory view showing one example of the transfer operation performed by the repeating device of embodiment 2; and

FIG. 6 is an explanatory view showing the minimum system environment in which the LAN telephone and the repeating device operate.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

The preferred embodiments of the present invention will now be explained.

FIGS. 1 through 6 are referred to in explaining the embodiments of the telephone and the repeating device according to the present invention. FIG. 1 is an explanatory view showing the functional structure of the logical block of the LAN telephone according to embodiment 1. FIG. 2 is an explanatory view showing one example of the transfer operation by the LAN telephone according to embodiment 1. FIG. 3 is an explanatory view showing an example where the transfer cannot be performed by the LAN telephone of embodiment 1. FIG. 4 is an explanatory view showing the functional structure of the logical block of the repeating device according to embodiment 2. FIG. 5 is an

explanatory view showing one example of the transfer operation by the repeating device of embodiment 2. FIG. 6 is an explanatory view showing the minimum system environment in which the LAN telephone and the repeating device operate.

Embodiment 1 will now be explained. The telephone according to the present embodiment comprises a function for requesting to another receiver-side telephone to reply their availability to connect a call, and a function for notifying the address of the receiver-side telephone that responded to the caller-side telephone. As shown in the functional structure of the logical block in FIG. 1, the telephone 12 according to the present embodiment comprises a CPU 121 having a structure of a microcomputer that facilitates the send-receive of communication data by controlling the whole unit, a RAM 122 functioning as a memory for logical memory, an EEPROM 123 which is a storage memory, an LED 124 and an LCD 125 that show the status of the present unit, a subscriber line (ISDN) and a 10 BASE-T (LAN), and a clock 126. Further, the present telephone comprises a LAN controller 127 that controls the send-receive data with the 10 BASE-T (LAN), and a controller 128 for physically controlling the 10 BASE-T. The telephone further comprises a microphone 129 and a speaker 130 for controlling the voice from the exterior. As shown in FIG. 6, the minimum system environment in which the LAN telephone according to the present embodiment functions is the same as the conventional example, wherein the PCs 11 and the LAN

telephones 12a-12c connected to the receiver-side LAN 10 are connected via the router 14, the ISDN 3, and connecting lines 41 and 42 to the PCs 21 and the LAN telephones 22a-22c connected to the caller-side LAN 20.

One example of the transfer operation according to the telephone of embodiment 1 will now be explained with reference to FIG. 2. When the receiver-side LAN telephone 12a which is the telephone according to the present embodiment is communicating with the caller-side LAN telephone 22a and the telephone 12a receives a transfer order from the user (in the present example, the LAN telephone 12b is designated as the transfer destination), the LAN telephone 12a sends a confirmation signal to check the availability of the LAN telephone 12b which is the designated transfer destination, and waits for a reply. The transfer-destination LAN telephone 12b rings a bell, and if the user answers the bell, it returns a "reply (call available)" to the LAN telephone 12a (in the example, the LAN telephone 12b is available for the call). Upon receiving the call available reply, the LAN telephone 12a notifies the address of the LAN telephone 12b to the caller-side LAN telephone 22a. The caller-side telephone 22a disconnects the call with the LAN telephone 12a, terminating the communication with the receiver-side LAN telephone 12a. The caller LAN telephone 22a generates a call to the address of the LAN telephone 12b, and when the transfer-destination LAN telephone 12b receives the call, it returns a "reply (call OK)".

Upon receiving the "reply (call OK)", the caller LAN telephone 22a starts the communication using the VoIP protocol, and the transfer process is completed. Thus, the LAN telephone 12a being connected to a call can confirm whether another receiver LAN telephone 12b is capable of receiving a transferred call, and the caller LAN telephone 22a can communicate with the LAN telephone 12b to which the call is transferred.

FIG. 3 is used to explain the case according to the telephone of embodiment 1 in which the transfer-side telephone does not return a reply. During communication with the caller-side LAN telephone 22a, when the receiver-side LAN telephone 12a receives a transfer order from the user (in this example, the LAN telephone 12b is designated as the transfer destination), it outputs a confirmation addressed to the transfer-destination LAN telephone 12b and waits for a reply. The transfer-destination LAN telephone 12b rings a bell, but since there is no reply from the user, the receiver-side LAN telephone 12a ceases the transfer confirmation process, and returns to the communication with the caller-side LAN telephone 22a, and disconnects when terminating the call.

Embodiment 2 will now be explained. The repeating device according to embodiment 2 comprises a function for requesting upon receiving a transfer request from a user a reply to another receiver-side telephone whether it is available for a call or not, and a function for notifying the address of the receiver-side telephone that responded to the caller-side

telephone. The functional structure of the logical block of the router 14 according to the present embodiment comprises, as shown in FIG. 4, a CPU 141 having a structure of a microcomputer that facilitates the send-receive of communication data by controlling the whole unit, a RAM 142 functioning as a memory for logical memory, an EEPROM 143 which is a storage memory, an LED 144 and an LCD 145 that show the status of the present unit, a subscriber line (ISDN) and a 10 BASE-T (LAN), and a clock 146. The router 14 further comprises a controller 150 that physically controls the subscriber line (ISDN), a controller 151 that physically controls the 10 BASE-T, and a controller 152 that physically controls the RS-232C. Moreover, the router 14 comprises a network controller 147 and a 10 BASE-T controller 151 for controlling the data being sent to or received from the subscriber line (ISDN), a LAN controller 148 that controls the data being sent to or received from the 10 BASE-T (LAN), and a RAM 149 which is used as the memory in which the network controller 147 or the LAN controller 148 store the send-receive data. The minimum system environment in which the repeating device of embodiment 2 operates is similar to embodiment 1 as shown in FIG. 6, so the explanation thereof is omitted.

One example of the operation of the repeating device according to embodiment 2 will now be explained with reference to FIG. 5. When a call is connected between the caller-side LAN telephone 22a and the receiver-side LAN telephone 12a, the

receiver-side LAN telephone 12a receives a transfer request from a user and the transfer destination is designated (in the present example, LAN telephone 12b is designated). The receiver-side LAN telephone 12a outputs a transfer request to the receiver-side router 14 addressed to the LAN telephone 12b. Upon receiving the transfer request, the receiver-side router 14 outputs a confirmation to the address of the transfer-side LAN telephone connected to the LAN 10 asking its availability to connect a call, and waits for a reply. The transfer-side LAN telephone 12b rings a bell, and if the user responds, returns a "reply (call available)" to the router 14 (in this case, the telephone 12b is available). Upon receiving the call available signal, the router 14 notifies the address of the transfer-side LAN telephone 12b to the caller-side LAN telephone 22a. Upon receiving the address of the transfer-side LAN telephone 12b, the caller-side LAN telephone 22a generates a call to the address of the transfer-side LAN telephone 12b. The transfer-side LAN telephone 12b receives the call, and returns a "reply (call OK)". The caller-side LAN telephone 22a receives the "reply (call OK)", and starts communication using VoIP protocol, and thus the transfer is completed. As explained, the repeating device, upon receiving a transfer request from a user, can confirm whether the transfer-side LAN telephone 12b is available for receiving the transferred call, and the caller-side LAN telephone 22a can communicate with the transfer-side LAN telephone 12b.

The above embodiments explained the case in which the present invention is applied to a telephone and a repeating device, but it is also possible to store to a recording medium (such as a CD-ROM) readable by a computer and storing a program to be performed by the computer the function for requesting upon receiving the transfer request from the user a response from another receiver-side telephone indicating whether it is available for connecting a call and a function for notifying the address of the receiver-side telephone that responded to the caller-side telephone, or a function for requesting during communication a response from another receiver-side telephone whether it is available to receive a call and a function for notifying the address of the receiver-side telephone that responded to the caller-side telephone. By using this recording medium, the telephone connected to a local area network or a device relaying communication to a plurality of receiver-side telephones connected to a local area network can function as the telephone or the repeating device of the present invention.

According to the present invention, in a communication system enabling communication between LAN telephones by providing a repeating device in a local area network or by relaying local area networks that have different subnet addresses with a communication line, the present invention enables to provide a telephone and a repeating device that are capable of transferring the call connected to a LAN telephone

to another LAN telephone.

TOP SECRET